## **TOSHIBA**

## **Wide Cash Drawer Technical Specifications**

HARDWARE			
Drawer Stability	Slide/Bracket asm support on both left and right side of drawer		
Construction	Slide bracket support with molded drawer. Molded color/texture. UV stable PC/ABS housing		
Colors	Black		
Interface	SDL (24V) with open/close drawer status or USB		
Till	2 Till OptionsFixed Till or Adjustable Till included with Wide Cash Drawer. No separate coin option.		
Document storage	Below till		
Supported Weight	Up to 100 lbs. (45.35 kg) - Enough for second drawer/sys unit and IO's.		
Serviceability	Easy to remove latch plate, and covers		
Security	High quality lock with multiple combo's Not readily opened by prying, riffing, etc.		
Life	2.0 Million. No preventative maintenance		
Materials Selection	Meets Toshiba UV / Materials requirements All plastics PC/ABS except mechanism plate and pawl		
Safety - External	Worldwide certifications (carried by system units)		
Safety - Internal	Worldwide certifications (carried by system units)		
Toshiba Environmental Compliance	Yes		
Toshiba Smoke/Smell	Yes		
Toshiba Safety	Yes		
Fulfillment	Cash Drawer, till. Cash Drawer includes till in one carton. Cable and Lock selected separately and ship with system. Customer does integration.		
Environment Specs	0 to 45 C		
EMC	Worldwide certifications (carried by system units)		
Drivers	UPOS compatible – There are no native Windows drivers. User must load UPOS.		
Diagnostics	POS Diagnostics		
Publications	Covered in Toshiba end user documents and service manual		
Systems Management	Provides feedback to RMA (need to define items)		

ITEM	WIDTH	HEIGHT	DEPTH
Wide Cash Drawer (Black or Iron Gray)	17.4 in. (442 mm)	4.78 in. (121.5 mm)	18.7 in. (475 mm)

Updated November 2, 2021



There are two types of latch plate interfaces offered: USB latch plate and SDL latch plate.

1. USB latch plate provides a 1x8 latching cable interface for both Wide and Compact cash drawers. This interface facilitates attachment to PC cash solutions and eliminates the cash drawer drive circuitry in future system units.

<sup>2.</sup> SDL latch plate operates at 24V power.